

## Linx Black Bottling Ink 1058

Date of compilation: 15/08/2022


Revised: 14/02/2023

Version: 11 (Replaced 10)

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** Linx Black Bottling Ink 1058
- Other means of identification:**  
Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Printing ink  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
- |  |   |
|--|---|
| Linx Printing Technologies Ltd<br>Linx House, 8 Stocks Bridge Way, Compass Point Business Park<br>PE27 5JL St Ives - Cambridgeshire - UK<br>Phone: +44 (0) 1480 302100<br>sds@linx.co.uk<br>www.linxglobal.com | Supplier:<br>ITW Marking and Coding<br>1 Research Park Drive<br>St. Charles, MO 63304-5685 USA<br>800-526-2531 / 636-300-2000 |
| <b>1.4 Emergency telephone number:</b> 24HR: (+1)-352-323-3500<br>USA: 1-800-535-5053  | Emergency Phone Number:<br>Infotrac: 800-535-5053 (US)<br>+1-352-323-3500 (International)                                     |

### SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
- GB CLP Regulation:**  
Classification of this product has been carried out in accordance with GB CLP Regulation.  
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412  
Eye Irrit. 2: Eye irritation, Category 2, H319  
Flam. Liq. 2: Flammable liquids, Category 2, H225  
Repr. 1B: Reproductive toxicity, Category 1B, H360  
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
- GB CLP Regulation:**  
**Danger**
- 
- Hazard statements:**  
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.  
Eye Irrit. 2: H319 - Causes serious eye irritation.  
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.  
Repr. 1B: H360 - May damage fertility or the unborn child.  
STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313: IF exposed or concerned: Get medical advice/attention.  
P370+P378: In case of fire: Use ABC powder extinguisher to put it out.  
P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively.
- Supplementary information:**  
EUH066: Repeated exposure may cause skin dryness or cracking.  
EUH208: Contains Aziridine, homopolymer, N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction.
- Substances that contribute to the classification**  
Butanone; Dye (1:2 Chromium (III) Complex)
- 2.3 Other hazards:**



## Linx Black Bottling Ink 1058

Date of compilation: 15/08/2022

Revised: 14/02/2023

Version: 11 (Replaced 10)

### SECTION 2: HAZARDS IDENTIFICATION (continued)

Product fails to meet PBT/vPvB criteria

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

**Chemical description:** Mixture of substances

#### Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 78-93-3	<b>Butanone</b> Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	60 - <80 %
CAS: 117527-94-3	<b>Dye (1:2 Chromium (III) Complex)</b> Aquatic Chronic 2: H411; Repr. 1B: H360 - Danger	5 - <10 %
CAS: 64-17-5	<b>ethanol</b> Eye Irrit. 2: H319; Flam. Liq. 2: H225 - Danger	1 - <5 %
CAS: 8047-99-2	<b>N-ethyl-o(or p)-toluenesulphonamide</b> Aquatic Chronic 3: H412	1 - <5 %
CAS: 1760-24-3	<b>N-(3-(trimethoxysilyl)propyl)ethylenediamine</b> Eye Dam. 1: H318; Skin Sens. 1: H317 - Danger	0.1 - <1 %
CAS: 9002-98-6	<b>Aziridine, homopolymer</b> Acute Tox. 4: H302; Aquatic Chronic 2: H411; Eye Dam. 1: H318; Skin Sens. 1: H317 - Danger	0.1 - <1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

#### Other information:

Identification	Specific concentration limit
ethanol CAS: 64-17-5	% (w/w) >=50: Eye Irrit. 2 - H319

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

##### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

##### By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

##### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

##### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

#### 4.2 Most important symptoms and effects, both acute and delayed:



## Linx Black Bottling Ink 1058

Date of compilation: 15/08/2022

Revised: 14/02/2023

Version: 11 (Replaced 10)

### SECTION 4: FIRST AID MEASURES (continued)

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media:

##### Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

##### Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

##### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

##### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

##### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

#### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

#### 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

**Linx Black Bottling Ink 1058**

Date of compilation: 15/08/2022

Revised: 14/02/2023

Version: 11 (Replaced 10)

**SECTION 7: HANDLING AND STORAGE (continued)**

**B.- Technical recommendations for the prevention of fires and explosions**

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in The Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations 2016 and with the minimum requirements for protecting the security and health of workers under the selection criteria of The Dangerous Substances and Explosive Atmospheres Regulations 2002, 2002 No. 2776. Consult section 10 for conditions and materials that should be avoided.

**C.- Technical recommendations on general occupational hygiene**

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

**D.- Technical recommendations to prevent environmental risks**

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

**A.- Technical measures for storage**

Store in a cool, dry, well-ventilated location

**B.- General conditions for storage**

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupational exposure limits		
	WEL (8h)	200 ppm	600 mg/m <sup>3</sup>
Butanone CAS: 78-93-3	WEL (15 min)	300 ppm	899 mg/m <sup>3</sup>
	WEL (8h)	1000 ppm	1920 mg/m <sup>3</sup>
ethanol CAS: 64-17-5	WEL (15 min)		

**Biological limit values:**

BIOLOGICAL MONITORING GUIDANCE VALUES (BMGVs) - EH40/2005

Identification	NULL	NULL	NULL
Butanone CAS: 78-93-3	5 mg/L	Butan-2-one in urine	Post shift

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	1161 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	600 mg/m <sup>3</sup>	Non-applicable
Dye (1:2 Chromium (III) Complex) CAS: 117527-94-3 EC: 938-781-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0.13 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0.94 mg/m <sup>3</sup>	Non-applicable

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
ethanol CAS: 64-17-5 EC: 200-578-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	343 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	950 mg/m <sup>3</sup>	Non-applicable
N-ethyl-o(or p)-toluenesulphonamide CAS: 8047-99-2 EC: 232-465-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	13.5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	19.1 mg/m <sup>3</sup>	Non-applicable

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Butanone CAS: 78-93-3 EC: 201-159-0	Oral	Non-applicable	Non-applicable	31 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	412 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	106 mg/m <sup>3</sup>	Non-applicable
Dye (1:2 Chromium (III) Complex) CAS: 117527-94-3 EC: 938-781-3	Oral	Non-applicable	Non-applicable	0.07 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0.07 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0.23 mg/m <sup>3</sup>	Non-applicable
ethanol CAS: 64-17-5 EC: 200-578-6	Oral	Non-applicable	Non-applicable	87 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	206 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	114 mg/m <sup>3</sup>	Non-applicable
N-ethyl-o(or p)-toluenesulphonamide CAS: 8047-99-2 EC: 232-465-2	Oral	Non-applicable	Non-applicable	1.6 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	8.1 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	5.65 mg/m <sup>3</sup>	Non-applicable

**PNEC:**

Identification				
Butanone CAS: 78-93-3 EC: 201-159-0	STP	709 mg/L	Fresh water	55.8 mg/L
	Soil	22.5 mg/kg	Marine water	55.8 mg/L
	Intermittent	55.8 mg/L	Sediment (Fresh water)	284.74 mg/kg
	Oral	1 g/kg	Sediment (Marine water)	284.7 mg/kg
ethanol CAS: 64-17-5 EC: 200-578-6	STP	580 mg/L	Fresh water	0.96 mg/L
	Soil	0.63 mg/kg	Marine water	0.79 mg/L
	Intermittent	2.75 mg/L	Sediment (Fresh water)	3.6 mg/kg
	Oral	0.38 g/kg	Sediment (Marine water)	2.9 mg/kg
N-ethyl-o(or p)-toluenesulphonamide CAS: 8047-99-2 EC: 232-465-2	STP	6.44 mg/L	Fresh water	0.078 mg/L
	Soil	0.292 mg/kg	Marine water	0.0078 mg/L
	Intermittent	0.78 mg/L	Sediment (Fresh water)	1.69 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.169 mg/kg
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3 EC: 217-164-6	STP	25 mg/L	Fresh water	0.062 mg/L
	Soil	0.009 mg/kg	Marine water	0.006 mg/L
	Intermittent	0.62 mg/L	Sediment (Fresh water)	0.22 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.022 mg/kg

**8.2 Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection


**Linx Black Bottling Ink 1058**

Date of compilation: 15/08/2022


Revised: 14/02/2023

Version: 11 (Replaced 10)

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**


Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands



Pictogram	PPE	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

**Appearance:**

Physical state at 20 °C: Liquid  
 Appearance: Fluid  
 Colour: Black  
 Odour: Characteristic

\*Not relevant due to the nature of the product, not providing information property of its hazards.



## Linx Black Bottling Ink 1058

Date of compilation: 15/08/2022

Revised: 14/02/2023

Version: 11 (Replaced 10)

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Odour threshold:	Non-applicable *
<b>Volatility:</b>	
Boiling point at atmospheric pressure:	81 °C
Vapour pressure at 25 °C:	9888 Pa
Vapour pressure at 50 °C:	29894.54 Pa (29.89 kPa)
Evaporation rate at 25 °C:	>1
<b>Product description:</b>	
Density at 25 °C:	882.5 kg/m <sup>3</sup>
Relative density at 25 °C:	0.812 - 0.952
Dynamic viscosity at 25 °C:	2 - 5 cP
Kinematic viscosity at 25 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 25 °C:	2.4 kg/m <sup>3</sup>
Partition coefficient n-octanol/water 25 °C:	ca. 0.3
Solubility in water at 25 °C:	Non-applicable *
Solubility properties:	Slightly soluble in cold water
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	-86 °C
<b>Flammability:</b>	
Flash Point:	6 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	>210 °C
Lower flammability limit:	1.8 % Volume
Upper flammability limit:	11.5 % Volume
<b>Particle characteristics:</b>	
Median equivalent diameter:	Non-applicable

#### 9.2 Other information:

##### Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

##### Other safety characteristics:

Surface tension at 25 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

#### 10.2 Chemical stability:

- CONTINUED ON NEXT PAGE -



## Linx Black Bottling Ink 1058

Date of compilation: 15/08/2022

Revised: 14/02/2023

Version: 11 (Replaced 10)

### SECTION 10: STABILITY AND REACTIVITY (continued)

Chemically stable under the indicated conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

##### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

##### A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

##### B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

##### C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

##### D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: propan-2-ol (3); ethanol (1); 2-phenylpropene (2B); styrene (2A)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: May damage fertility or the unborn child

##### E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

##### F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

##### G- Specific target organ toxicity (STOT)-repeated exposure:

- CONTINUED ON NEXT PAGE -



**Linx Black Bottling Ink 1058**

Date of compilation: 15/08/2022

Revised: 14/02/2023

Version: 11 (Replaced 10)

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	Route	Dose	
Butanone CAS: 78-93-3	LD50 oral	4000 mg/kg	Rat
	LD50 dermal	6400 mg/kg	Rabbit
	LC50 inhalation	23.5 mg/L (4 h)	Rat
ethanol CAS: 64-17-5	LD50 oral	6200 mg/kg	Rat
	LD50 dermal	20000 mg/kg	Rabbit
	LC50 inhalation	124.7 mg/L (4 h)	Rat
Dye (1:2 Chromium (III) Complex) CAS: 117527-94-3	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
Aziridine, homopolymer CAS: 9002-98-6	LD50 oral	680 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	

**Acute Toxicity Estimate (ATE mix):**

ATE mix		Ingredient(s) of unknown toxicity
Oral	>5000 mg/kg (Calculation method)	Non-applicable
Dermal	>5000 mg/kg (Calculation method)	Non-applicable
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Toxicity:**

**Acute toxicity:**

Identification	Concentration		Species	Genus
	Route	Dose		
Butanone CAS: 78-93-3	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish
	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae
Dye (1:2 Chromium (III) Complex) CAS: 117527-94-3	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
ethanol CAS: 64-17-5	LC50	11000 mg/L (96 h)	Alburnus alburnus	Fish
	EC50	9268 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1450 mg/L (192 h)	Microcystis aeruginosa	Algae
N-ethyl-o(or p)-toluenesulphonamide CAS: 8047-99-2	LC50	>10 - 100 mg/L (96 h)		Fish
	EC50	>10 - 100 mg/L (48 h)		Crustacean
	EC50	>10 - 100 mg/L (72 h)		Algae

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Concentration		Species	Genus
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3	LC50	597 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	81 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	8.8 mg/L (72 h)	Selenastrum capricornutum	Algae
Aziridine, homopolymer CAS: 9002-98-6	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae

**Chronic toxicity:**

Identification	Concentration		Species	Genus
ethanol CAS: 64-17-5	NOEC	250 mg/L	Danio rerio	Fish
	NOEC	2 mg/L	Ceriodaphnia dubia	Crustacean

**12.2 Persistence and degradability:**

**Substance-specific information:**

Identification	Degradability		Biodegradability	
Butanone CAS: 78-93-3	BOD5	2.03 g O2/g	Concentration	Non-applicable
	COD	2.31 g O2/g	Period	20 days
	BOD5/COD	0.88	% Biodegradable	89 %
Dye (1:2 Chromium (III) Complex) CAS: 117527-94-3	BOD5	Non-applicable	Concentration	20 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	14.1 %
ethanol CAS: 64-17-5	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	89 %
N-(3-(trimethoxysilyl)propyl)ethylenediamine CAS: 1760-24-3	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	39 %

**12.3 Bioaccumulative potential:**

**Substance-specific information:**

Identification	Bioaccumulation potential	
Butanone CAS: 78-93-3	BCF	3
	Pow Log	0.29
	Potential	Low
Dye (1:2 Chromium (III) Complex) CAS: 117527-94-3	BCF	
	Pow Log	2.29
	Potential	
ethanol CAS: 64-17-5	BCF	3
	Pow Log	-0.31
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
Butanone CAS: 78-93-3	Koc	30	Henry	5.77 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.396E-2 N/m (25 °C)	Moist soil	Yes
Dye (1:2 Chromium (III) Complex) CAS: 117527-94-3	Koc	18	Henry	Non-applicable
	Conclusion	Very High	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
ethanol CAS: 64-17-5	Koc	1	Henry	4.61E-1 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.339E-2 N/m (25 °C)	Moist soil	Yes

**12.5 Results of PBT and vPvB assessment:**

Product fails to meet PBT/vPvB criteria

**Linx Black Bottling Ink 1058**

Date of compilation: 15/08/2022

Revised: 14/02/2023

Version: 11 (Replaced 10)

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class
08 03 12*	waste ink containing hazardous substances	Dangerous

**Type of waste:**

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste Regulations 2011.

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2021 and RID 2021:



- 14.1 UN number:** UN1210
- 14.2 UN proper shipping name:** PRINTING INK
- 14.3 Transport hazard class(es):** 3
- Labels:** 3
- 14.4 Packing group:** II
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
  - Tunnel restriction code: D/E
  - Physico-Chemical properties: see section 9
  - Limited quantities: 5 L
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 40-20:

**Linx Black Bottling Ink 1058**

Date of compilation: 15/08/2022

Revised: 14/02/2023

Version: 11 (Replaced 10)

**SECTION 14: TRANSPORT INFORMATION (continued)**



<b>14.1 UN number:</b>	UN1210
<b>14.2 UN proper shipping name:</b>	PRINTING INK
<b>14.3 Transport hazard class(es):</b>	3
Labels:	3
<b>14.4 Packing group:</b>	II
<b>14.5 Marine pollutant:</b>	No
<b>14.6 Special precautions for user</b>	
Special regulations:	367, 163
EmS Codes:	F-E, S-D
Physico-Chemical properties:	see section 9
Limited quantities:	5 L
Segregation group:	Non-applicable
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2023:



<b>14.1 UN number:</b>	UN1210
<b>14.2 UN proper shipping name:</b>	PRINTING INK
<b>14.3 Transport hazard class(es):</b>	3
Labels:	3
<b>14.4 Packing group:</b>	II
<b>14.5 Environmental hazards:</b>	No
<b>14.6 Special precautions for user</b>	
Physico-Chemical properties:	see section 9
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Non-applicable

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Non-applicable
- Substances listed in UK REACH Authorisation List (Annex 14): Non-applicable

**Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc ....):**

Product classified hazardous under the CMR. Sale and distribution to the general public is prohibited. Due to its CMR category, it is essential to apply the specific measures for workplace hazard prevention covered in articles 4 and 5 of the 2004/37/EC Directive and later modifications.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

- The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.
- The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.
- Control of Substances Hazardous to Health Regulations 2002 (as amended)
- EH40/2005 Workplace exposure limits.



## Linx Black Bottling Ink 1058

Date of compilation: 15/08/2022

Revised: 14/02/2023

Version: 11 (Replaced 10)

### SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

#### Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects.

H336: May cause drowsiness or dizziness.

H360: May damage fertility or the unborn child.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### GB CLP Regulation:

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Repr. 1B: H360 - May damage fertility or the unborn child.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT SE 3: H336 - May cause drowsiness or dizziness.

#### Classification procedure:

Aquatic Chronic 3: Calculation method

STOT SE 3: Calculation method

Repr. 1B: Calculation method

Flam. Liq. 2: Calculation method (2.6.4.3)

Eye Irrit. 2: Calculation method

#### Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

#### Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -