

**1. Identification**

**Product identifier** **GPX Grizzly & 2018-P Auto Mark (All Colors)**  
**Other means of identification** None.  
**Recommended use** Marking.  
**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Company name** Diagraph Marking and Coding  
**Address** 5307 Meadowland Parkway Marion IL 62959  
**Telephone** 1-800-521-3047  
**E-mail** msds@diagrammsp.com  
**Contact person** Customer Service  
**Emergency phone number** Emergency telephone 800-535-5053 (US only)  
+1-352-323-3500 international

**2. Hazard(s) identification**

**Physical hazards** Flammable liquids Category 2  
**Health hazards** Serious eye damage/eye irritation Category 2A  
Specific target organ toxicity, single exposure Category 3 respiratory tract irritation  
Specific target organ toxicity, single exposure Category 3 narcotic effects  
**OSHA defined hazards** Not classified.

**Label elements**



**Signal word** Danger  
**Hazard statement** Highly flammable liquid and vapor. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.  
**Precautionary statement**  
**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear protective gloves/eye protection/face protection. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area.  
**Response** If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. In case of fire: Use appropriate media to extinguish.  
**Storage** Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.  
**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.  
**Hazard(s) not otherwise classified (HNOC)** None known.  
**Supplemental information** None.

**3. Composition/information on ingredients**

**Mixtures**

Chemical name	CAS number	%
Proprietary Co Solvent B	Trade Secret	15-30
Ethyl lactate	97-64-3	10-15
Ethyl alcohol	64-17-5	10-15
Terpenes and Terpenoids, turpentine-oil, .alpha.-pinene fraction, polymers with phenol	259094-71-8	10-15
1-Methoxy-2-propanol	107-98-2	1-5
Titanium dioxide	13463-67-7	0-30
Carbon black	1333-86-4	0-10
Kaolin, calcined	92704-41-1	0-5

**Composition comments** All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

<b>Inhalation</b>	Move injured person into fresh air and keep person calm under observation. If necessary, seek hospital and take along these instructions.
<b>Skin contact</b>	Take off contaminated clothing and wash before reuse. Wash off with warm water and soap. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Rinse with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	Rinse mouth thoroughly. Only induce vomiting at the instruction of medical personnel. Get medical attention if any discomfort continues.
<b>Most important symptoms/effects, acute and delayed</b>	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause respiratory irritation. Coughing. Vapors may cause drowsiness and dizziness. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
<b>Indication of immediate medical attention and special treatment needed</b>	In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	The product is highly flammable, and explosive vapor/air mixtures may be formed even at normal room temperatures. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back.
<b>Special protective equipment and precautions for firefighters</b>	Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Highly flammable liquid and vapor.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. For personal protection, see section 8 of the SDS.
--	--

**Methods and materials for containment and cleaning up**

Extinguish all flames in the vicinity. Stop leak if you can do so without risk. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. Clean up in accordance with all applicable regulations. For waste disposal, see Section 13 of the SDS.

**Environmental precautions**

Avoid discharge into drains, water courses or onto the ground unless authorized by permit.

**7. Handling and storage****Precautions for safe handling**

Do not smoke and do not spray near an open flame or other sources of ignition. Vapors are heavier than air and may travel along the floor and in the bottom of containers. Vapors may be ignited by a spark, a hot surface or an ember. The product is highly flammable, and explosive vapor/air mixtures may be formed. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid sparks and prevent accumulation of electrostatic charges. Provide adequate ventilation. Local exhaust is recommended. Observe good industrial hygiene practices.

**Conditions for safe storage, including any incompatibilities**

Follow rules for flammable liquids. Do not store near heat sources or expose to high temperatures. Keep away from heat, sparks and open flame. Store in a closed container away from incompatible materials.

**8. Exposure controls/personal protection****Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Ethyl alcohol (CAS 64-17-5)	PEL	1900 mg/m3 1000 ppm	
Proprietary Co Solvent B (CAS Trade Secret)	PEL	710 mg/m3 150 ppm	
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
1-Methoxy-2-propanol (CAS 107-98-2)	STEL	100 ppm	
Carbon black (CAS 1333-86-4)	TWA	50 ppm	
Ethyl alcohol (CAS 64-17-5)	TWA	3.5 mg/m3	Inhalable fraction.
Proprietary Co Solvent B (CAS Trade Secret)	STEL	1000 ppm	
	STEL	200 ppm	
	TWA	150 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
1-Methoxy-2-propanol (CAS 107-98-2)	STEL	540 mg/m3
		150 ppm
	TWA	360 mg/m3
		100 ppm
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3

## US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ethyl alcohol (CAS 64-17-5)	TWA	1900 mg/m3 1000 ppm
Proprietary Co Solvent B (CAS Trade Secret)	STEL	950 mg/m3
	TWA	200 ppm 710 mg/m3 150 ppm

**Biological limit values** No biological exposure limits noted for the ingredient(s).

### Exposure guidelines

#### US - California OELs: Skin designation

1-Methoxy-2-propanol (CAS 107-98-2) Can be absorbed through the skin.

**Appropriate engineering controls** Observe Occupational Exposure Limits and minimize the risk of inhalation. Explosion-proof general and local exhaust ventilation. Provide easy access to water supply and eye wash facilities.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear approved safety goggles.

#### Skin protection

**Hand protection** For prolonged or repeated skin contact use suitable protective gloves. Suitable gloves can be recommended by the glove supplier. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

**Other** Wear appropriate clothing to prevent repeated or prolonged skin contact.

**Respiratory protection** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with combination filter. Seek advice from local supervisor.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

**Physical state** Liquid.

**Form** Liquid.

**Color** Various.

**Odor** Not available.

**Odor threshold** Not available.

**pH** Not available.

**Melting point/freezing point** Not available.

**Initial boiling point and boiling range** Not available.

**Flash point** 62.0 °F (16.7 °C) (Solvent Blend)

**Evaporation rate** Not available.

**Flammability (solid, gas)** Not available.

### Upper/lower flammability or explosive limits

**Flammability limit - lower (%)** Not available.

**Flammability limit - upper (%)** Not available.

**Explosive limit - lower (%)** Not available.

<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.

## 10. Stability and reactivity

<b>Reactivity</b>	Stable at normal conditions.
<b>Chemical stability</b>	The product is stable and non reactive under normal conditions of use, storage and transport.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Contact with incompatible materials. Keep away from heat, sparks and open flame.
<b>Incompatible materials</b>	Strong oxidizing agents. Strong acids. Strong bases.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause respiratory tract irritation.
<b>Skin contact</b>	Causes mild skin irritation. Repeated exposure may cause skin dryness or cracking.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	May cause discomfort if swallowed.

**Symptoms related to the physical, chemical and toxicological characteristics** Symptoms may include redness, drying and cracking of the skin. Exposed individuals may experience eye tearing, redness, and discomfort. May cause respiratory irritation. Vapors may cause drowsiness and dizziness. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

### Information on toxicological effects

**Acute toxicity** May cause discomfort if swallowed.

Components	Species	Test Results
1-Methoxy-2-propanol (CAS 107-98-2)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rat	> 2000 mg/kg
<i>Oral</i>		
LD50	Rat	3739 mg/kg
Ethyl alcohol (CAS 64-17-5)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	39 g/m <sup>3</sup> , 4 Hours
<i>Oral</i>		
LD50	Rat	7000 - 11000 mg/kg
Proprietary Co Solvent B (CAS Trade Secret)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Rat	2000 ppm, 4 Hours
<i>Oral</i>		
LD50	Rat	10768 mg/kg

<b>Skin corrosion/irritation</b>	Causes mild skin irritation. Prolonged or repeated contact may dry skin and cause dermatitis.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	No data available.
<b>Skin sensitization</b>	Not a skin sensitizer.
<b>Germ cell mutagenicity</b>	No data available.
<b>Carcinogenicity</b>	Inhalation of carbon black or titanium dioxide dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Carbon black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
<b>NTP Report on Carcinogens</b>	
Not listed.	
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
Not listed.	
<b>Reproductive toxicity</b>	No data available.
<b>Specific target organ toxicity - single exposure</b>	May cause respiratory irritation. May cause drowsiness or dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	No data available.
<b>Aspiration hazard</b>	No data available.
<b>Chronic effects</b>	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. The product contains organic solvents which may be absorbed into the body by skin contact and cause permanent damage to the nervous system, including the brain.

## 12. Ecological information

**Ecotoxicity** The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Ethyl alcohol (CAS 64-17-5)		
<b>Aquatic</b>		
Crustacea	LC50	Ceriodaphnia dubia
		Daphnia magna
	NOEC	Ceriodaphnia dubia
Fish	LC50	Pimephales promelas

**Persistence and degradability** No data available.

### Bioaccumulative potential

#### Partition coefficient n-octanol / water (log Kow)

Ethyl alcohol (CAS 64-17-5)	-0.31
Proprietary Co Solvent B	1.78

**Mobility in soil** No data available.

**Other adverse effects** An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

## 13. Disposal considerations

**Disposal instructions** Dispose in accordance with all applicable regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 °F

**Waste from residues / unused products** Dispose of in accordance with federal, state, and local regulations.

**Contaminated packaging** Since emptied containers retain product residue, follow label warnings even after container is emptied.

## 14. Transport information

### DOT

UN number	UN1210
UN proper shipping name	Printing ink, flammable
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, IB2, T4, TP1, TP8
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

### IATA

UN number	UN1210
UN proper shipping name	Printing ink flammable
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

### IMDG

UN number	UN1210
UN proper shipping name	PRINTING INK flammable
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## 15. Regulatory information

**US federal regulations** This product is hazardous according to OSHA 29 CFR 1910.1200.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

### CERCLA Hazardous Substance List (40 CFR 302.4)

1-Methoxy-2-propanol (CAS 107-98-2) LISTED

Proprietary Co Solvent B (CAS Trade Secret) LISTED

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

<b>Hazard categories</b>	Immediate Hazard - Yes
	Delayed Hazard - No
	Fire Hazard - Yes
	Pressure Hazard - No
	Reactivity Hazard - No

### SARA 302 Extremely hazardous substance

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**SARA 313 (TRI reporting)**  
Not regulated.

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**  
Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**  
Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**US state regulations** WARNING: This product contains chemical(s) known to the State of California to cause cancer.

**US. Massachusetts RTK - Substance List**

1-Methoxy-2-propanol (CAS 107-98-2)  
Carbon black (CAS 1333-86-4)  
Ethyl alcohol (CAS 64-17-5)  
Ethyl lactate (CAS 97-64-3)  
Proprietary Co Solvent B (CAS Trade Secret)  
Titanium dioxide (CAS 13463-67-7)

**US. New Jersey Worker and Community Right-to-Know Act**

1-Methoxy-2-propanol (CAS 107-98-2)  
Carbon black (CAS 1333-86-4)  
Ethyl alcohol (CAS 64-17-5)  
Ethyl lactate (CAS 97-64-3)  
Proprietary Co Solvent B (CAS Trade Secret)  
Titanium dioxide (CAS 13463-67-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

1-Methoxy-2-propanol (CAS 107-98-2)  
Carbon black (CAS 1333-86-4)  
Ethyl alcohol (CAS 64-17-5)  
Ethyl lactate (CAS 97-64-3)  
Proprietary Co Solvent B (CAS Trade Secret)  
Titanium dioxide (CAS 13463-67-7)

**US. Rhode Island RTK**

Proprietary Co Solvent B (CAS Trade Secret)

**US. California Proposition 65**

Not Listed.

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

**Issue date** 30-October-2013  
**Revision date** 31-January-2019  
**Version #** 02  
**HMIS® ratings** Health: 2  
Flammability: 3  
Physical hazard: 0



**NFPA ratings****Disclaimer**

Diagraph MSP cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.