

# GP-X CLASSIC

**VALVE ACTION** | **ALL PURPOSE PAINT MARKER**

## FEATURES:

- Replaceable tips extend the life of your markers.
- Clearly marks on dark or light surfaces.
- Available in 13 weather & fade resistant colors.
- Valve Action markers allow control of paint flow while keeping the paint in the barrel from drying-out when the cap is off.
- Great for metal, wood, corrugated, rubber, plastic, glass and other hard to mark surfaces.
- Sold by color in boxes of 12. Cartons include 12 boxes / 144 markers.
- Black and White meet nuclear specs RDT-F7-3T, rev. 5.1
- Minimum of 60% renewable content.
- No hazardous air pollutants.

## COMPATIBILITY:

- Safe for most porous & non-porous surfaces.
- Test on surfaces prior to use to ensure compatibility.

## DIRECTIONS FOR USE:

- Shake marker well with the cap on
- Twist the cap off
- Gently pump until the tip is primed

## TECH SPECS:

- Standard Stroke Width: 1/8"
- Fill Quantity: ~1/2 oz (~12 cc)
- Barrel Size: .563" Diameter x 4.75" Long

## HEALTH & SAFETY:

- Use only with proper ventilation.
- Flammable liquid & vapor: keep away from ignition sources like flames, sparks, or electrostatic charges.
- Avoid skin and eye contact and ingestion.
- No Reportable Prop 65
- Flash Point: 62°F (17°C)
- For complete health & safety data, refer to SDS at [www.diaggraphmsp.com](http://www.diaggraphmsp.com)

## PHYSICAL PROPERTIES:

| Color       | Part No. | Specific Gravity | VOC Level   | Total Halogens | Approx. Dry Time |
|-------------|----------|------------------|-------------|----------------|------------------|
| White       | 0960500  | 1.22             | 5.6 lbs/gal | < 57 ppm       | 20-30 Sec        |
| Yellow      | 0960501  | 1.22             | 6.3 lbs/gal | 126 ppm        | 20-30 Sec        |
| Black       | 0960502  | 0.96             | 5.3 lbs/gal | < 64 ppm       | 20-30 Sec        |
| Blue        | 0960503  | 1.03             | 7.0 lbs/gal | < 24 ppm       | 20-30 Sec        |
| Red         | 0960504  | 1.02             | 5.6 lbs/gal | < 200 ppm      | 20-30 Sec        |
| Green       | 0960505  | 1.14             | 6.5 lbs/gal | 42 ppm         | 20-30 Sec        |
| Pink        | 0960506  | 1.19             | 5.4 lbs/gal | < 200 ppm      | 20-30 Sec        |
| Gold        | 0960507  | 1.01             | 6.0 lbs/gal | < 200 ppm      | 20-30 Sec        |
| Brown       | 0960508  | 1.02             | 6.3 lbs/gal | 39 ppm         | 20-30 Sec        |
| Light Green | 0960509  | 1.21             | 5.9 lbs/gal | 53 ppm         | 20-30 Sec        |
| Orange      | 0960510  | 1.01             | 6.0 lbs/gal | 43 ppm         | 20-30 Sec        |
| Purple      | 0960511  | 1.17             | 5.8 lbs/gal | 73 ppm         | 20-30 Sec        |
| Silver      | 0960512  | 0.95             | 5.2 lbs/gal | < 200 ppm      | 20-30 Sec        |